

SERVICE 361 UPGRADE

100 % USA MADE FOR 361 VALVES.

Sanitary Solutions NOW OFFERS A 361 UPGRADE CONSISTING OF OUR "SERVICE 7" REPAIRABLE ACTUATOR AND A VALVE STEM WITH A REPLACEABLE SEAT ASSEMBLY ELIMINATING THE QUICK COUPLER. IT IS A DIRECT CLAMP-ON ASSEMBLY FOR ANY MAKE OF THE 1.5", 2", 2.5" AND 3" 361 VALVE.

- INCREASED HOLDING PRESSURES.
185 PSI FOR THE 1.5" VALVE.

100 PSI FOR THE 2.5" VALVE.
75 PSI FOR THE 3" VALVE.
- CONTROL TOP READY, FIELD REVERSIBLE PATENT PENDING SERVICE 7 REPAIRABLE ACTUATOR THAT IS BUILT TO LAST.
- DIRECT CLAMP-ON FOR ALL MAKES OF 361 VALVES. NO SPECIAL TOOLS OR MACHINING REQUIRED.
- NO MORE CONSTANTLY REPLACING THE VALVE STEM AND PLUG BECAUSE THE TIP OF THE VALVE STEM WAS RUINED BY THE QUICK COUPLER.
- BETTER RIGIDITY OF THE VALVE STEM AS IT IS THREADED ON THE ACTUATOR SHAFT.
- VALVE STEM USES THE SAME REPLACEABLE SEAT OFFERED BY YOUR LOCAL DISTRIBUTOR.

CONTACT **SANITARY SOLUTIONS** and ask for WESTERN ACTUATION ACTUATORS!



SERVICE 7 ACTUATOR

100 % USA MADE FOR 761/741 VALVES.

- "SAFE" CAPTIVE SPRING-TENSION RELEASE DESIGN.
- INCREASED HOLDING PRESSURES.
- STAINLESS STEEL CONSTRUCTION BUILT TO LAST.
- FIELD SERVICEABLE WITH LOW COST SEAL KIT.
- FIELD REVERSIBLE ACTUATION.
- DIRECT REPLACEMENT, AND CONTROL TOP READY.
- CUSTOM SPRINGS FOR SPECIAL HOLDING PRESSURES.
- CORROSION RESISTANT SS COMPONENTS.
- COMPETITIVELY PRICED-HUGE SAVINGS COMPARED TO OEM THROW AWAY ACTUATORS. WHY REPLACE WHEN YOU CAN SERVICE?
- DESIGN PATENT PENDING.
- SHORT AND LONG STROKE FOR 1.5 THRU 4 INCH VALVES. 4" AND 6" DIAMETER ACTUATORS.
- NO SPECIAL TOOLS REQUIRED.



Sanitary Solutions is pleased to announce the addition of more actuators to our line of repairable actuators for the 700 series of valves as follows:

25-436-S (750318) Short Stroke 4" diameter standard for 761 - 1.5" - 3" valves, ao/sc
 25-438-S (751681) Long Stroke 4" diameter for 761 - 1.5" - 3" valves, ao/sc
 25-497-S (750496) Short Stroke 6" diameter standard for 761 - 3" - 4" valves, ao/sc
 25-467-S (751391) Long Stroke 6" diameter for 761 - 3" - 4" valves, ao/sc
 25-465-S (750043) Short Stroke 4" diameter for 761 - 1.5" - 3" valves, ao/ac
 25-446-S (751823) Long stroke 4" diameter for 761 - 1.5" - 3" valves, ao/ac
 25-457-S (750384) Standard 6" diameter for 761 - 2" Y-body valves, ao/sc
 25-468-S (759635) Special long stroke 6" diameter for 761 - 90 - 3" - 4" valves, ao/ac
 25-517-S (751719) Standard long stroke 6" diameter for 761 - 3" - 4" valves, ao/ac
 25-519-S (751987) Short stroke 6" diameter for 761 - 3" - 4" valves, ao/ac